

Termination Box MOTB-X48A

Feature:

- Up to 48 drop cables
- Up to 54 simplex SC adaptors
- Can accommodate up to 6 pieces 1 x 8, 1 x 16 and 1 x 32 PLC Splitter
- Maximum capacity is 144F (6 trays)
- The maximum capacity of splice trays is 24 fibers
- The oval port is for 1 loop cable or 2 cables with max Ø 20 mm.
- The reserved port is for cables with max Ø 18 mm
- The twelve ports with diameter Ø 14 mm, each port can hold 4 drop cables
- Bending radius > 30 mm
- Outdoor use IP 65
- Designed for Wall and Pole mount applications
- Safety lock
- Rugged and durable construction for long term reliability (UV resistance)
- Design for small and medium volumes of fiber optic cables
- Reusable
- RoHS compliance
- Dimensions (L x W x H): 398 x 327 x 118 mm



Specification:

Model No	Cable Port	Adaptors	PLC splitter
MOTB-X48A	The Oval port is for 1 loop cable or 2 cables with max Ø 20 mm. The reserved port is for cables with max Ø 18 mm The twelve ports with diameter Ø 14 mm, each port can hold 4 drop cables, totally 48 drop cables	54 SC adaptors	up to 6 pieces 1 x 8, 1 x 16 or 1 x 32 PLC Splitter